



## **Single Beam UV VIS Spectrophotometer TRSUV-601**

[www.shakerdeals.com](http://www.shakerdeals.com) | [info@shakerdeals.com](mailto:info@shakerdeals.com)

## Description

Single Beam UV VIS Spectrophotometer TRSUV-601 is a versatile device with blazed holographic gratings and an 8-inch multi-color touch-screen that allows for the setting and viewing of parameters with such a wavelength range of 190 to 1100 nm and then a frequency band bandwidth of 2 nm. The automated 8-position cuvette holder makes the operation mode easier. It has a photometric accuracy of 0.3 % T, 0.002Abs (0 to 0.5A), and a range of 0.0 to 200.0 % T, -0.301 to 4.000A, and 0.000 to 9999 C. It performs admirably in both qualitative and quantitative testing and has a stray light of ? 0.03%.

## Features:

- 8-inch multi-color touch-screen, advanced user interface, powerful functions, and simple operation
- It uses a split-beam survey optical system as well as a blazed holographic display
- Scanning the entire spectrum
- Linear regression analysis
- Extensive frequency band scanning
- Persistence of time-based kinetics
- Measurement of multiple wavelengths
- The zero and full scales are automatically adjusted. A USB port is included
- Gratings they have exceptional test precision and very competitive pricing
- The automated 8-position cuvette holder makes operation easier in each measurement mode
- With its powerful functions, the equipment performs admirably in both qualitative and quantitative testing

## Specifications :

<b>Baseline Drift</b>	$\pm 0.0009$ Abs / h (250 nm and 500 nm after preheat warm up for 2 hours )
<b>Baseline Flatness</b>	? $\pm 0.002$ A
<b>COM Port</b>	USB
<b>Detector</b>	Silicon Photocell
<b>Focal Length</b>	160 mm
<b>Grating</b>	1200 lines/mm
<b>Monochromatic Type</b>	Czerny-Turner
<b>Noise</b>	100%(T) noise ? 0.15% (T), 0% (T) noise ? 0.1% (T)
<b>Packing Size</b>	740 mm×630 mm×450 mm
<b>Photometric Accuracy</b>	$\pm 0.3\%$ T $\pm 0.002$ Abs (0 to 0.5A) $\pm 0.004$ Abs (0.5 to 1A)
<b>Photometric Range</b>	0.0 to 200.0% T -0.301 to 4.000A 0.000 to 9999C
<b>Photometric Repeatability</b>	? 0.15% T 0.001Abs (0 to 0.5A) 0.002Abs (0.5 to 1A)
<b>Photometry</b>	Split Beam
<b>Power</b>	AC 220 V $\pm$ 22 V, 50 Hz $\pm$ 1 Hz, 200 W
<b>Spectrum Bandwidth</b>	2 nm
<b>Stray Light</b>	? 0.03% (measured by NaI at 220 nm) (measured at NaNO <sub>2</sub> at 360 nm)
<b>Wavelength Accuracy</b>	$\pm 0.5$ nm
<b>Wavelength Range</b>	190 to 1100 nm
<b>Wavelength Repeatability</b>	? 0.2 nm
<b>Wavelength Scanning Speed</b>	Fast, medium, slow
<b>Weight</b>	0.21m <sup>3</sup> , 35kg



Dallas Parkway Plano TX 75093, USA  
Email: [info@shakerdeals.com](mailto:info@shakerdeals.com) | Website: [www.shakerdeals.com](http://www.shakerdeals.com)