



Single Beam UV VIS Spectrophotometer TRSUV-603

www.shakerdeals.com | info@shakerdeals.com

Description

Single Beam UV VIS Spectrophotometer TRSUV-603 is a versatile device with blazed holographic gratings and an 8-inch multi-color touch-screen that allows for the setting and viewing of parameters with such a wavelength range of 325 to 1100 nm and then a frequency band bandwidth of 2 nm. The automated 8-position cuvette holder makes the operation mode easier. It has a photometric accuracy of $\pm 0.5\%$ and a range of 0.0 to 200.0 % T, -0.301 to 4.000A, and 0.000 to 9999 C. It performs admirably in both qualitative and quantitative testing and has a stray light of $\approx 0.03\%$.

Features:

- 8-inch multi-color touch-screen, advanced user interface, powerful functions, and simple operation
- It uses a split-beam survey optical system as well as a blazed holographic display
- Scanning the entire spectrum
- Linear regression analysis
- Extensive frequency band scanning
- Persistence of time-based kinetics
- Measurement of multiple wavelengths
- The zero and full scales are automatically adjusted. A USB port is included
- Gratings they have exceptional test precision and very competitive pricing
- The automated 8-position cuvette holder makes operation easier in each measurement mode
- With its powerful functions, the equipment performs admirably in both qualitative and quantitative testing

Specifications :

Baseline Drift	± 0.0009 Abs / h (500 nm after preheat warm up for 2 hours)
Baseline Flatness	? ± 0.002 A
COM Port	USB
Detector	Silicon Photocell
Focal Length	160 mm
Grating	1200 lines/mm
Monochromatic Type	Czerny-Turner
Noise	100%(T) noise ? 0.2% (T), 0% (T) noise ? 0.1% (T)
Packing Size	740 mm×630 mm×450 mm
Photometric Accuracy	± 0.5 % T
Photometric Range	0.0 to 200.0 % T -0.301 to 4.000 A 0.000 to 9999 C
Photometric Repeatability	? 0.2 % T
Photometry	Split Beam
Power	AC 220 V \pm 22 V, 50 Hz \pm 1 Hz, 120 W
Spectrum Bandwidth	2 nm
Stray Light	? 0.05 % (measured at NaNO ₂ at 360 nm)
Wavelength Accuracy	± 0.5 nm
Wavelength Range	325 to 1100 nm
Wavelength Repeatability	? 0.2 nm
Wavelength Scanning Speed	Fast, medium, slow
Weight	0.21m ³ , 35kg



Dallas Parkway Plano TX 75093, USA
Email: info@shakerdeals.com | Website: www.shakerdeals.com